


VGP880M 50Hz POWERED BY PERKINS SERIES



TECHNICAL SPECIFICATIONS

DIESEL GENERATING SET 400/230V-50Hz-3Phase

Model	VGP880M	
Power(ESP)	kVA/kw	880/704
Power(PRP)	kVA/kw	800/640
Starter Voltage	V	24
Rated Current	A	1271
Rated rotation speed	r/min	1500
Power Factor		0.8
Fuel Consumption	Litre/hour	172
Fuel Tank Capacity	Litre	Open Type : L / Silent Type: L
Noise level	dB(A)@7m	Silent Type: 88±2

WEIGHT AND DIMENSIONS

GEN-Set	Dimension (L*W*H)	Weight
Open Type	4300mm*1720mm*2172mm	5744Kg
Silent Type	6058mm*2438mm*2591mm	8922Kg

STANDARDS:

Genset: GB/T2820—2009,ISO8528

Alternator: MECC ALTE, ECO43 1S4A

Diesel Engine: PERKINS , 4006-23TAG3A

Standby Power: Continues running at variable load for duration of an emergency. No overload is permitted on these ratings.

Prime Power: Continues running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period.

CONFIGURATION:

Standard: Engine, alternator, cooling system, Base frame (excluding fuel tank), shock absorber, air inlet system, control box (including mains floating charge), plastic fan blades (when the engine and water tank do not bring).

Optional: Base frame (including fuel tank), water jacket heater, fuel water separator, fuel heater, fuel level sensor (only supporting underframe tank), switch box (with switch), power switch, the water level sensor, motor anti condensation heater, automatic fueling system (only supporting base frame including fuel tank), battery frame.

Accessories: Silencer, bellow, exhaust silencing system accessories (with the matching engine), regular battery, starting cord assembly, data of gen-set, random tool (with the matching engine).



ENGINE Specification

Manufacturer: PERKINS

Model	4006-23TAG3A
Engine speed Rated	1500 RPM
Cylinder /Arrangement	6/ L
Displacement	22.921L
Bore and Stroke	160mm × 190mm
Compression ratio	13.6: 1
Max. stand by power at rated RPM	786KW
Frequency regulation , steady state	≤0.25%
Governor : type	Electrical

Exhaust System

Exhaust gas flow	193L/min
Exhaust temperature	500°C
Max back pressure	

Fuel System

Fuel consumption100% (of the Prime Power)	172L / h
Fuel consumption75% (of the Prime Power)	130L / h
Fuel consumption50% (of the Prime Power)	90L / h
Fuel consumption25% (of the Prime Power)	

Oil system

Total oil capacity w/filters	113.4L
------------------------------	--------

Air intake

Engine air flow	73L/min
-----------------	---------

Coolant System

Radiator & engine capacity	105 L
Max water temperature	98°C
Thermostat	71-85°C



- ☐ Perkins engines with fast and reliable cold boost.
- ☐ Advanced technology on burning Combustion optimization, low fuel consumption and low noise, emission meets German TALuft standard.
- ☐ Reasonable coupling creates best compounding function, provides reliable and high-performance power products.
- ☐ Integrated structure of generator with fuel tank and base frame and internal high-efficiency anti-vibration.

Note: All data sheets are for reference only and subject to change without prior notice.



Control Panel

Model: DSE 7320

AUTO START & AUTO MAINS FAILURE CONTROL MODULES

DIMENSIONS

OVERALL

240mm x 181mm x 42mm
(9.4" x 7.1" x 1.6")

PANEL CUTOOUT

220mm x 160mm
(8.7" x 6.3")

WEIGHT

400g (0.4kg)



KEY FEATURES

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Tier 4 CAN engine support
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Engine exerciser
- "Protections disabled" feature
- kW & kV Ar protection

- Reverse power (kW & kV Ar) protection
- LED and LCD alarm indication
- Power monitoring (kW h, kV Ar, kVA h, kV Ar h)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Unbalanced load protection
- Independent Earth Fault trip
- True dual mutual standby with load balancing timer (DSE7310 only)
- USB connectivity
- Backed up real time clock
- Fully configurable via DSE Configuration Suite PC software
- Configurable display languages
- Remote SCADA monitoring via DSE Configuration Suite PC software
- User selectable RS232 and RS485 communications
- Configurable Gencomm pages
- Advanced SMS messaging (additional external modem required)
- Start & stop capability via SMS messaging
- Additional display screens to

- help with modem diagnostics
- Idle control for starting & stopping.
- DSENet® expansion compatible

KEY BENEFITS

- 132 x 64 pixel ratio display for clarity
- Real-time clock provides accurate event logging
- Multiple date and time scheduler
- Set maintenance periods can be configured to maintain optimum engine performance
- Ethernet communications (via DSE860/865 modules), provides advanced remote monitoring at low cost
- Modules can be integrated into building management systems(BMS)
- Increased input and output expansion capability via DSENet®
- Licence-free PC software
- IP65 rating (with supplied gasket) offers increased resistance to water ingress
- PLC editor allows user configurable functions to meet specific application requirements.